

Amendments to the Claims

WE CLAIM:

1. (Currently Amended) A moment-resistant column/beam structural system comprising
an elongate column,
an elongate beam, and
collar structure including an integrated, column-axis-circumsurrounding portion anchored to said beam, and connecting an end of said beam to said column inwardly toward the outside of the column via compression through plural, confronting bearing faces that are distributed angularly about the long axis of the column.

2. (Currently Amended) The structural system of claim 1, wherein said collar structure includes a column-attachable (CA) member attached to said column, and a beam-end-attachable member (BA) forming at least a part of said integrated, column-axis-circumsurrounding portion, attached to said beam and floatingly seated principally under the influence of gravity on said CA member.

Sub
b1

3. (Currently Amended) A self-stabilizing, moment-resistant, collar-form, elongate-column/elongate-beam interconnect structure for use in a building comprising
a collar-form column-attachable (CA) member including plural, laterally outwardly facing, sloping, interconnection bearing faces, and
a collar-form beam-end-attachable (BA) member including plural, laterally outwardly facing, sloping, interconnection bearing faces,
said CA and BA members being constructed for seated interconnection in a manner whereby gravity causes their respective bearing faces to seat self-seekingly and complementarily relative to one another in confronting, bearing-face opposition, thereby to establish nominal, three-dimensional, lateral positional and moment-resistant stability between the two members without the requirement for any other interconnecting structure.

Art

4. (Original) The interconnect structure of claim 3, wherein said CA and BA members include complementarily mateable cleat and socket structure.

5. (Cancelled)

6. (Cancelled)

7. (Currently Amended) A building structure restable on an external support structure comprising

Q2K
a plurality of upright columns distributed, as seen in plan view, in a row-and-column array, with columns in said array intended to act as load-transfer elements for the transfer of all loads from the building structure to the external support structure,

a plurality of generally horizontal beams, each extending between different respective pairs of said columns, and

multi-axial, three-dimensional, moment-resistant, collar-form interconnect structure including inner and outer collar members each disposed outwardly, and each circumsurrounding the long axis, of a column, operatively interconnecting said columns and beams at locations of adjacency therebetween in such a manner that all loads introduced into the building structure are borne substantially throughout the full population of columns and beams, and specifically in a manner whereby such loads are delivered to and responsively shared by all of the load-transferring columns.

b1
cont

8. (Currently Amended) Moment-resistant, spatial-position-determining and stabilizing interconnect structure for interconnecting, during the preliminary construction of a building, the end of an elongate, generally horizontal beam to an elongate, generally upright column, said interconnect structure, in operative condition, comprising

203

a first, inner, interconnect collar structure anchored to such a column circumsurroundingly relative to the column's long axis, and including first, gravity-utilizing, outwardly facing, sloping, bearing-face substructure, and

second, outer, interconnect collar structure anchored adjacent the end of such a beam, and including second, gravity-utilizing, inwardly facing, sloping, bearing-face substructure,

said second, bearing-face substructure being seatingly mateable, under the influence of gravity, on and with respect to said first bearing-face substructure during preliminary building construction to establish a gravity-locked and stabilized, moment-resistant interconnection between the associated column and beam, which interconnection tends to create, independently, the correct spatial disposition of the column and beam in the building.

9. (Currently Amended) A column/beam, moment-load-handling method comprising preparing an elongate column, at a selected location along its length, with plural, compression-reception bearing surfaces distributed at plural, different locations spaced angularly about the column's long axis,

adjacent the column's mentioned selected location, coupling an end of an elongate beam thereto through plural, compression-delivery bearing surfaces which bear against, but which are separate from, different ones of the first-mentioned bearing surfaces, and

with respect to moment loads that are experienced by the beam, delivering such loads to the column via compression developed simultaneously between plural ones of the compression-reception and the compression-delivery bearing surfaces.

10. (Original) Moment-resistant interconnect structure for establishing a three-dimensional, multi-axial, moment-coupling, load-transfer interconnection and interaction between an elongate column and an elongate beam, said interconnect structure comprising inner collar structure selectively anchorable to such a column circumsurroundingly relative to the column's long axis, and

outer collar structure selectively joinable to an end of such a beam, and constructed for discontinuous, circumsurrounding, bearing-face coupling to said inner collar structure for the compression transfer of moment loads between the associated beam and column.

11. (Original) A moment-resistant, bearing-face, load-transfer interconnection between an elongate column and an elongate beam, said interconnection, in operative condition, comprising

a first bearing-face structure joined to such a column to form an inner collar structure which generally circumsurrounds the column's long axis, said first bearing-face structure including plural bearing faces each facing outwardly relative to, and at different locations spaced angularly about, the column's long axis,

second bearing-face structure joined to an end in such a beam to form an outer collar structure which also generally circumsurrounds the column's long axis, and which is disposed as a jacket surrounding said inner collar structure, said second bearing-face structure including plural bearing faces each opposingly facing at least one of said bearing faces in said first bearing-face structure, and

connector structure operatively connecting said first and second bearing-face structures in a manner whereby the opposing bearing faces in said first and second bearing-face structures confrontingly oppose one another to promote compression load transfer therebetween, and thus between the column and the beam, with such load transfer being derived from moment loads carried in said beam.

b1
cont

12. (Currently Amended) Gravity-lock, self-positioning and stabilizing, moment-frame building structure comprising

plural elongate columns each equipped, at one or more locations along their respective lengths, with axially circumsurrounding inner collar structure which includes first-gender, gravity-effective cleat structure including laterally outwardly facing sloping face structure, and

2
cont

plural elongate beams each attached, adjacent opposite ends, to outer collar structure which includes second-gender, gravity-effective cleat structure that is mateable, under the influence of gravity, complementarily with said first-gender cleat structure, said second-mentioned cleat structure including laterally inwardly facing, sloping face structure which is complementarily contactable with said first-mentioned sloping face structure.

gravity-mating of said first- and second-gender cleat and sloping face structures creating therebetween, and thus between the associated column and beam, a gravity-locked, stabilized, correctly relatively positioned, moment-resistant interconnection between that column and beam.

13. (Currently Amended) A moment-resistant column/beam structural system comprising
a column,
a beam, and

interconnect structure operatively interposed and interconnecting an end of the beam to the column in a manner whereby moment loads borne by the beam are delivered to the outside of the column substantially solely through the interconnect structure, and simultaneously at plural regions that are distributed angularly about the long axis of the column.

14. (Currently Amended) A multi-axial, two-dimensional, moment-resistant building structure including plural columns, plural beams, and plural interconnect collars which interconnect adjacent columns and beams at nodes, whereby all loads introduced into the structure are distributed and borne throughout the entire structure, with each load delivered by each beam to a column delivered thereto simultaneously to the outside of the column at plural locations distributed about the long axis of the column.

15. (Original) The building structure of claim 14, wherein said collars are configured whereby moment loads present in beams are distributed to the columns through the collars in the form of bearing-face compression.

b1
cont

16. (New) A self-stabilizing, moment-resistant, collar-form, elongate-column/elongate-beam interconnect structure for use in a building comprising

a collar-form beam-end-attachable (BA) member including plural, operatively associated, bolt-interconnected components possessing plural interconnection bearing faces, and

a collar-form column-attachable (CA) member including plural, operatively associated components having plural bolt-clearance passages and possessing plural interconnection bearing faces,

03

said BA and CA members being constructed for seated interconnection in a manner whereby gravity causes their respective components' bearing faces to seat self-seekingly and complementarily relative to one another in confronting, bearing-face opposition, thereby to establish nominal, three-dimensional, positional and moment-resistant stability between the two members without the requirement for any other interconnecting structure, said BA and CA members, when so seated relative to one another, and with respect to bolts which include shanks interconnecting said BA members, being positionally related in a manner whereby the shanks in said bolts extend within said clearance passages to impeded unseating of the BA and CA members.

b1
cont

17. (New) A self-stabilizing, moment-resistant, collar-form, elongate-column/elongate-beam interconnect structure for use in a building comprising

a collar-form column-attachable (CA) member including plural interconnection bearing faces,
and

a collar-form beam-end-attachable (BA) member including plural interconnection bearing faces,

Q3
Q4

said CA and BA members being constructed for seated interconnection in a manner whereby gravity causes their respective bearing faces, which faces each lies in a plane which slopes downwardly and away from a column long axis, to seat self-seekingly and complementarily relative to one another in confronting, bearing-face opposition, thereby to establish nominal, three-dimensional, positional and moment-resistant stability between the two members without the requirement for any other interconnecting structure.
